

ISO/API Casing Products Catalogue

Label ^a		Outside Diameter	Norminal Linear Masses T&C	Wall Thickness	Type of End-finish			
		D mm	Kg/m	t mm	J55 K55	L80	N80 -1 N80-Q	P110
4-1/2	9.50	114.30	14.14	5.21	S	—	—	—
4-1/2	10.50	114.30	15.63	5.69	SB	—	—	—
4-1/2	11.60	114.30	17.26	6.35	SLB	LB	LB	LB
4-1/2	13.50	114.30	20.09	7.37	—	LB	LB	LB
4-1/2	15.10	114.30	22.47	8.56	—	—	—	LB
5	11.50	127.00	17.11	5.59	S	—	—	—
5	13.00	127.00	19.35	6.43	SLB	—	—	—
5	15.00	127.00	22.32	7.52	SLB	LB	LB	LB
5	18.00	127.00	26.79	9.19	—	LB	LB	LB
5	21.40	127.00	31.85	11.10	—	LB	LB	LB
5	23.20	127.00	34.53	12.14	—	LB	LB	LB
5	24.10	127.00	35.86	12.70	—	LB	LB	LB
5-1/2	14.00	139.70	20.83	6.20	S	—	—	—
5-1/2	15.50	139.70	23.07	6.98	SLB	—	—	—
5-1/2	17.00	139.70	25.30	7.72	SLB	LB	LB	LB
5-1/2	20.00	139.70	29.76	9.17	—	LB	LB	LB
5-1/2	23.00	139.70	34.23	10.54	—	LB	LB	LB
6-5/8	20.00	168.28	29.76	7.32	SLB	—	—	—
6-5/8	24.00	168.28	35.72	8.94	SLB	LB	LB	LB
6-5/8	28.00	168.28	41.67	10.59	—	LB	LB	LB
6-5/8	32.00	168.28	47.62	12.06	—	LB	LB	LB
7	17.00	177.80	25.30	5.87	—	—	—	—
7	20.00	177.80	29.76	6.91	S	—	—	—
7	23.00	177.80	34.23	8.05	SLB	LB	LB	—
7	26.00	177.80	38.69	9.19	SLB	LB	LB	LB
7	29.00	177.80	43.16	10.36	—	LB	LB	LB
7	32.00	177.80	47.62	11.51	—	LB	LB	LB
7	35.00	177.80	52.09	12.65	—	LB	LB	LB
7-5/8	24.00	193.68	35.72	7.62	—	—	—	—
7-5/8	26.40	193.68	39.29	8.33	SLB	LB	LB	LB
7-5/8	29.70	193.68	44.20	9.52	—	LB	LB	LB
7-5/8	33.70	193.68	50.15	10.92	—	LB	LB	LB
7-5/8	39.00	193.68	58.04	12.70	—	LB	LB	LB
7-5/8	42.80	193.68	63.69	14.27	—	LB	LB	LB
7-5/8	45.30	193.68	67.41	15.11	—	LB	LB	LB